

### SPK 2x4.00 mm<sup>2</sup> speaker (50240)

Flexible speaker cable for power amplifiers up to 2750 watts. 51 strands of 0.30 mm bare copper wires, stranding for best flexibility but still affordable price.

Best cost effectiveness yet still flexible construction. Easy application to most connectors. Cotton strands to keep the cable construction round and stable.

same product as PVC-version available: 50040



FRNC = Flame Retardant Non Corrosive = Flame retardant per IEC-332-1 test standard

1	Jacket	FRNC compound, $\varnothing$ 9.4 mm, black; separation viscose fiber coat
2	Insulation	Polyolefin, $\varnothing$ 3.9 mm, black and red; filler: cotton rope
3	Conductor	(OFC) Stranded bare copper wires 224 x 0.15 mm (4.00 mm <sup>2</sup> )

Center conductor resistance	< 4.65 Ohm /km	Test voltage cond/cond	2000 V eff.
Insulation resistance	> 200 MOhm /km	Operating voltage	300 V
Power rating	2750 Watt	Temperature range (flex)	- 5° to +50° C
Current max.	24.0 Ampere	Temperature range (fix)	-30° to +70° C
		Bending radius min.	5x overall diam.

Order No.	Type	$\varnothing$ mm	Color	Spool Size	Weight /Spool	Shipping Unit
50240	SPK 2x4.00 mm <sup>2</sup>	9.4	black	100 m	15.3 kg	1 x 100 m